



Dry



Wet



Heat



Oily



Cold



Chemical



TG3210

A lightweight PU Cut Index B glove compliant to EN388:2016. The close fitting design, good abrasion and tear resistance and grip makes it an ideal choice for most general handling tasks in dry conditions.

Key Features

- Close fitting and breathable PU glove
- Good durability and grip in dry conditions
- Available with 3 exposed fingertips if further dexterity required

Ideal for

- Automotive
- Construction and Utility
- Engineering and Manufacturing
- Warehousing and Logistics

Sizes:	6-12	Gauge:	13gg
Liner:	Polyamide/HPPE	Coating:	X-Dura PU
No/Bag:	10	No/Carton:	100

TG3210

Glove Specifications

Glove lengths
220mm-270mm

Glove Weight
13 gauge

Liner Type
Polyamide/HPPE

Glove colour
Pantone 158c / R:245 G:127 B:498 / C:2 M:63 Y:100 K:0

Overlock Colours

SIZE	XS-6	S-7	M-8	L-9	XL-10	2XL-11	3XL-12
COLOUR	BLUE	RED	ORANGE	WHITE	YELLOW	BLACK	GREEN

Coating Specifications

Coating colour
Black

Dip type
Polyurethane

Dip Application
Palm Dipped

Glove Treatment
X-Dura



Packaging Information

Qty/bag
10 pairs

Qty/carton
100 pairs

Carton Dimensions
300mm x 600mm x 200mm

Maintenance

Both new and used gloves should be inspected to ensure no damage is present prior to use. A light gentle wash up to 3 washing cycles with mild detergent without involvement of any sort of bleaching agents. No tumble drying, just line dry at low temperature up to 30 degree Celsius.

Storage

Gloves should be ideally stored in cool, dry conditions away from excessive heat and in its original packaging.

Disposal

Used protective gloves can be contaminated or infected with harmful substances. Dispose of the gloves as instructed by your local authority.