

Rayza RX552

Lightweight Polyurethane Coated Index E Glove



SPECIFICATION & CHARACTERISTICS

Code RX552

Size Range 6/XS-11/XXL

Packaging 10 pairs/pack - 100 pairs/carton

Palm Coating Silicone-free polyurethane

Lining HPPE

Characteristics

- ✓ High quality cut resistant liner with outstanding mechanical performance.
- ✓ Ultra lightweight liner provides comfort and dexterity.
- ✓ Touch screen compatibility.
- ✓ Unique silicone-free polyurethane coating provides excellent durability.
- ✓ Ideal for working in dry or slightly oily conditions.

STANDARDS COMPLIANCE

EN388: 2016

Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut* (Coup)	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
E = Cut (EN ISO 13997)	(Rating A-F)

NOTES:

Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

*Gloves should not be used when working with serrated blades.



4X42E