



# Rayza RX565

## Double Dipped Nitrile Coated Cut Level 5 Glove

### SPECIFICATION & CHARACTERISTICS

Code	RX565
Size Range	6/XS - 11/XXL
Packaging	10 pairs/pack - 10 packs/case
Palm Coating	Textured Nitrile
Liner	18 gauge HPPE liner with Nitrile coating

#### Characteristics

- ✓ Excellent resistance to oils and greases.
- ✓ Excellent mechanical resistance.
- ✓ High filament count for enhanced dexterity and softer feel.
- ✓ Outstanding grip.
- ✓ Good Flexibility.
- ✓ Providing a high level of cut resistance.
- ✓ Double dipped for increased durability.

### STANDARDS COMPLIANCE

#### EN388:2016

#### Mechanical Hazards

Protection against mechanical hazards in respect of physical and mechanical stress caused by abrasion, blade cut, tear and puncture. The table below indicates the glove's resistance to:

4 = Abrasion	(Performance Index 1-4)
X = Blade Cut*	(Performance Index 1-5)
4 = Tear	(Performance Index 1-4)
2 = Puncture	(Performance Index 1-4)
D = Cut (EN ISO 13997)	(Rating A-F)

#### NOTES:

Where 1 indicates the lowest performance. X that the test was not performed or not possible. A 0 rating indicates that during the test level 1 was not reached.

\*Gloves should not be used when working with serrated blades.



4X42D